

Strong Gold Results Continue at Minos Prospect

Highlights

- First batch of assay results returned from December RC drill programme at Minos
- 15 RC drillholes completed for 2,310m
- Assays returned for 5 holes with significant results including:
 - 21m @ 3.14g/t Au from 75m, including 1m @ 19.70g/t Au and 1m @ 21.80g/t Au
 - o 25m @ 2.42g/t Au from 140m, including 2m @ 14.85g/t Au
 - 4m @ 4.14g/t Au from 43m, including 1m @ 10.00g/t Au
 - o 5m @ 1.26g/t Au from 24m
 - 4m @ 2.06g/t Au from 71m
 - o 2m @ 3.67g/t Au from 78m
- Awaiting assays from a further 10 holes
- Drilling data continues to assist with definition of high-grade gold zones
- Gold mineralisation confirmed over 600m strike length at Minos
- Gold mineralisation remains open along strike in both directions and at depth
- Assays also pending from calcrete sampling programme completed in December across the Partridge, Earea Dam and Ealbara Prospects
- Strong pipeline of exploration activity with further drilling planned for Minos and other key targets within Indiana's Central Gawler Craton Gold Project over coming months

Indiana Resources Limited (**ASX: IDA**) ('**Indiana' or the 'Company'**) is pleased to report further wide gold intersections from drilling recently completed at the Minos Prospect within Indiana's 100% owned 5,713 km² Central Gawler Craton Gold Project in South Australia.

A total of fifteen (15) drillholes for 2,310m were completed at Minos in December, with the programme designed to infill the existing drill hole coverage and provide further geological information for inclusion in the proposed resource estimate for Minos.

Assay results from five (5) Reverse Circulation (RC) drillholes have been received, with the remaining assays expected in March 2022.

Initial results confirm the Company's geological interpretation and reinforces that the Lake Labyrinth Shear Zone is a significant gold bearing system. It also confirms that Minos has potential for extension of the known mineralisation along strike in both directions and at depth.

434,940,960 Shares on Issue A\$0.062 Share Price 27M Market Cap Bronwyn Barnes Executive Chair Felicity Repacholi-Muir Technical Director Robert (Bob) Adam

Non-executive Director

Aida Tabakovic Joint Company Secretary Trevor Harris CFO & Company Secretary **CONTACT US**

+61 (8) 6241 1870 info@indianaresources.com.au www.indianaresources.com.au Suite 3, 339 Cambridge St, Wembley WA 6014



Company Comment

Indiana's Technical Director Felicity Repacholi-Muir said:

"Drilling at Minos continues to return highly encouraging zones of gold mineralisation, which supports our theory that Minos is a continuous orebody, remaining open both along strike and at depth. Each programme completed across our Lake Labyrinth Shear Zone targets has returned impressive gold results and highlighting the strong potential for a much larger gold system to be hosted.

We look forward to resuming our aggressive exploration campaign as soon as heavy vehicle access to our tenements is permitted following the rain event in South Australia earlier this year."




Figure 1: Minos Prospect – significant drilling results

Minos Results Summary

Drilling was designed to tighten the existing drill density, define some of the known high-grade zones and extend some known lodes at depth. Drilling was focused on the north-western portion of the orebody.

Drillholes LLRC074, LLRC075 and LLRC076 were completed on **Section 10,560mE** (local grid) designed to define the high-grade zone previous encountered in LLRCD028 (refer Figure 2). Significant results include:

- 5m @ 1.26 g/t Au from 24m in Hole LLRC074;
- 4m @ 2.06 g/t Au from 71m in Hole LLRC074;
- 2m @ 3.67 g/t Au from 78m in Hole LLRC074;





- 21m @ 3.14 g/t Au from 75m in Hole LLRC075 including 1m @ 19.70 g/t Au from 80m and 1m @ 21.80 g/t Au from 90m;
- 3m @ 2.81 g/t Au from 147m in Hole LLRC075;
- 25m @ 2.42 g/t Au from 140m in Hole LLRC076 including 2m @ 14.85 g/t Au from 140m

The results on Section 11,760mE illustrate that gold mineralisation is continuous from near surface and remains open at depth.




Figure 2: Minos Cross Section A-A'





Drillholes LLRC073 and LLRC077 were completed on sections where assays are pending from other drillholes in this current programme (see Figures 3 and 4).

Drillhole LLRC073 was completed along a new section designed to increase the drill density of the orebody. The drillhole was designed to test the downdip potential along **Section 11,815mE**, returning 11m @ 0.63g/t Au from 161m. The results from the other drillholes (LLRC070, LLRC071 and LLRC072) completed along this section are pending.

Drillhole LLRC077 was designed to test the up-dip extension on **Section 11,740mE** where LLRC039 had previously returned 6m @ 2.63g/t Au from 31m, 14m @ 0.88g/t Au from 40m and 5m @ 2.49g/t Au from 100m and LLRC041 had returned 21m @ 8.43 g/t Au from 176m including 1m @ 159 g/t Au from 185m and 2m @ 18.4 g/t Au from 162m in Hole LLRC041 including 1m @ 35.6 g/t Au from 163m.

LLRC077 intersected shallow gold mineralisation, returning 4m @ 4.14g/t Au from 43m including 1m @ 10.00g/t Au from 43m. Results from LLRC078 and LLRC079 on this Section are pending.

Next Steps

The laboratory in Adelaide has been experiencing a slower than usual turnaround given delays due to the impact of COVID on staffing levels, in addition to high demand and high-volume backlog. It is anticipated that assay results for the remaining ten (10) holes will be received in March 2022.

Also pending are the assay results from the calcrete sampling programme completed in December across the Partridge, Earea Dam and Ealbara Prospects. Results from this programme are expected to identify further gold anomalies, mineralisation trends and assist with drillhole targeting.

Indiana planned to recommence drilling at Minos in January, however this has been delayed due to the historically high rainfall in central South Australia which has damaged major roads and railway lines. Drilling will recommence when access to Indiana's tenements is suitable for heavy vehicles.

Indiana looks forward to advising the market when the remaining assays are received from the drilling completed at Minos.








Figure 3: Minos Cross Section B-B'








Figure 4: Minos Cross Section C-C'








Figure 5: Strike extent of prospective Lake Labyrinth Shear Zone





Technical information included in this announcement has previously been provided to the market in releases dated:

4th August 2020 Indiana to Acquire South Australia Gold Projects

28th September 2020 IDA Completes Acquisition of South Australian Gold Projects 27th January 2021 Completion of Drilling at Central Gawler Craton Gold Project

9th February 2021 Significant Au Results – Minos Diamond Hole

22nd February 2021 Exceptional High-Grade Gold Results at Minos Prospect

3rd March 2021 High Grade Gold Results Continue at Minos

23rd March 2021 Exploration Update

19th April 2021 Commencement of RC Drilling at Minos, Central Gawler Craton 3rd May 2021 Completion of Drilling at Central Gawler Craton Gold Project 24th June 2021 Exploration Update – Central Gawler Craton Gold Project 3th July 2021 Stunning High-Grade Gold Results Continue at Minos Prospect

12th August 2021 Aircore Drilling & Exploration Update

7th October 2021 Exploration Update

3rd November 2021 Further Diamond Assays Received from Minos

21st December 2021 Drilling Extends Mineralization at LLSZ
11th January 2022 Wide Gold Intersections Extend Minos Strike

Ends

This announcement is authorised for release to the market by the Technical Director of Indiana Resources Limited with the authority from the Board of Directors.

For further information, please contact:

Felicity Repacholi-Muir Trevor Harris
Technical Director Joint Compo
T: +61 (0) 409 997 879 T: +61 8 6241

Joint Company Secretary
T: +61 8 6241 1870

Aida Tabakovic Joint Company Secretary T: +61 8 94281 0389

To find out more, please visit <u>www.indianaresources.com.au</u>

Background

The Minos prospect is located within the Lake Labyrinth Shear Zone (LLSZ) and is interpreted to be a 30km long WNW- ESE trending regional structure that is at least 50 to 100 metres wide. The Minos and Ariadne prospects are located within the central part of the structure whilst the Partridge and North Hicks prospects are located at the WNW and ESE extensions respectively (Figure 5). There is no outcrop or workings at Minos and the entire area is covered by at least 1 to 2 metres of soil and calcrete. The only surface expression of mineralisation within the main LLSZ near Minos is at Ariadne.


The LLSZ is a major regional structure and the Company believes that it has acted as a pathway for ore forming fluids that produced the mineralisation at Minos and Ariadne. Indiana believes that the LLSZ may potentially host further zones of gold mineralisation and will be a major focus of future exploration.

The Minos prospect forms a part of Indiana's 100% owned exploration portfolio in the Central Gawler Craton of South Australia. With a tenement package comprising 5,713 km², Indiana acquired the ground in late 2020 and commenced exploration activity in early 2021. There remains a number of other high potential targets within the tenement portfolio and the Company is working through land access requirements in order to expand its exploration footprint in this exciting region.





The Central Gawler Craton has outstanding potential for the discovery of significant gold deposits, as indicated by the Tunkillia Gold Project (965,000 ounce gold resource), which adjoins the southern edge of the Company's tenements and the historical mining centre of Tarcoola, which adjoins the northern edge of the tenements, where historic production and current resources total approximately 93,000 ounces. Both Tarcoola and Tunkillia are now owned by Barton Gold Pty Ltd. In addition, Barton Gold also owns the Challenger Gold deposit, located 150 km North West of the tenement package which historically produced more than 1 million ounces.



Source: Barton Gold 1 Past production 1.2 Moz, current resource 65.6 koz; 2 Past production 77 koz, current resource 15.8 koz; 3 Current resource

Figure 6: Indiana's ground position in the Central Gawler Craton





Table 1: New significant Au intercepts included in this release \geq = 0.5 g/t Au

						0.0 9					
Site ID	Drill	MGA	MGA	RL	Dip	MGA	Total Depth	From	То	Length	Αu
0.10 12	Type	North	East		J.P	Azimuth	roral Depili	m	m	m	g/t
LLRC065	RC	6607973	495430	142	-60	210	96		Awai	ting Results	
LLRC066	RC	6607997	495444	142	-60	210	168	Awaiting Results			
LLRC067	RC	6607977	495410	142	-60	210	90	Awaiting Results			
LLRC068	RC	6607996	495421	142	-60	210	132	Awaiting Results			
LLRC069	RC	6608012	495431	142	-60	210	168	Awaiting Results			
LLRC070	RC	6607950	495444	142	-60	210	84		Awai	ting Results	
LLRC071	RC	6607969	495459	142	-60	210	126	Awaiting Results			
LLRC072	RC	6607993	495471	142	-60	210	186			ting Results	
LLRC073	RC	495493	6608006	145	-60	210	222	161	172	11	0.63
								181	182	1	0.85
								204	205	1	1.74
								208	209	1	0.58
								220	221	1	1.09
LLRC074	RC	495493	6607927	149	-60	210	90	24	29	5	1.26
								38	40	2	1.63
								43	44	1	0.52
								71	75	4	2.06
								78	80	2	3.67
LLRC075	RC	495509	6607949	149	-60	210	156	47	48	1	1.65
								75	96	21	3.14
							including	80	81	1	19.70
							including	90	91	1	21.80
								112	113	1	0.52
								115	116	1	0.70
								139	140	1	0.91
								147	150	3	2.81
LLRC076	RC	495527	6607979	149	-60	210	228	131	133	2	2.44
								140	165	25	2.42
							including	140	142	2	14.85
								179	180	1	0.56
								192	194	2	1.47
								200	201	1	0.50
								203	204	1	0.51
								207	208	1	0.95
LLRC077	RC	495507	6607907	150	-60	210	126	21	27	6	0.78
								43	47	4	4.14
								43	44	1	10.00
								52	55	3	0.63
								70	71	1	0.67
								84	86	2	2.06
LLRC078	RC	6607949	495532	142	-60	210	198		Awai	ting Results	
LLRC079	RC	6607968	495548	142	-60	210	240		Awai	ting Results	

Notes

>= 0.5 g/t Au composites and > 0.5m length allowing for 2 m of internal dilution

Trigger value >= 0.5 g/t Au, no top cut applied

Reported intersections are downhole lengths – true widths are unknown at this stage

Au analysis by fire assay, Bureau Veritas Adelaide, DL 0.01 ppm

Coordinates by GPS (positional accuracy approximately ±3m)

Competent Person Statement

The information in this report that relates to Exploration Results is based on information compiled or reviewed by Ms Felicity Repacholi-Muir, a Competent Person who is a Director of the Company. Ms Repacholi-Muir is a Member of the Australian Institute of Geoscientists and has sufficient experience of relevance to the styles of mineralisation and the types of deposits under consideration, and to the activities undertaken, to qualify as a Competent Person as defined in the 2012 Edition of the Joint Ore Reserves Committee (JORC) Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Ms Repacholi-Muir consents to the inclusion of the information in the form and context in which it appears.

The Company confirms that it is not aware of any new information or data that materially affects the Exploration Results information included in this report from previous Company announcements, including Exploration Results extracted from the Company's subsequent ASX announcements of 4th August 2020, 18th January 2021, 9th February 2021, 22nd February 2021, 3rd March 2021, 13th July 2021, 7th October 2021 and 3rd November 2021.





Forward Looking Statements

Indiana Resources Limited has prepared this announcement based on information available to it. No representation or warranty, express or implied, is made as to the fairness, accuracy, completeness or correctness of the information, opinions and conclusions contained in this announcement. To the maximum extent permitted by law, none of Indiana Resources Limited, its Directors, employees or agents, advisers, nor any other person accepts any liability, including, without limitation, any liability arising from fault or negligence on the part of any of them or any other person, for any loss arising from the use of this announcement or its contents or otherwise arising in connection with it. This announcement is not an offer, invitation, solicitation or other recommendation with respect to the subscription for, purchase or sale of any security, and neither this announcement nor anything in it shall form the basis of any contract or commitment whatsoever. This announcement may contain forward looking statements that are subject to risk factors associated with exploration, mining and production businesses. It is believed that the expectations reflected in these statements are reasonable but they may be affected by a variety of variables and changes in underlying assumptions which could cause actual results or trends to differ materially, including but not limited to price fluctuations, actual demand, currency fluctuations, drilling and production results, reserve estimations, loss of market, industry competition, environmental risks, physical risks, legislative, fiscal and regulatory changes, economic and financial market conditions in various countries and regions, political risks, project delay or advancement, approvals and cost estimate.

ANNEXURE 1:

The following Tables are provided to ensure compliance with JORC Code (2012) edition requirements for the reporting of the Exploration Results at the Central Gawler Craton Project.

SECTION 1: Sampling Techniques and Data (Criteria in this section apply to all succeeding sections)

	- · · · · · · · · · · · · · · · · · · ·			
Criteria	JORC Code explanation	Commentary		
Sampling techniques	Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure	Reverse Circulation drilling undertaken at the Minos prospect during December 2021. Drilling contractor was Bullion Drilling based in Port Augusta S.A. Rig type was a Schramm T450WS with a 700+psi compressor, bit size 140mm. Samples were collected at 1m intervals from an		
	sample representivity and the appropriate calibration of any measurement tools or systems used.	automatic splitter, average sample weight was ~2kg. Samples analysed for Au by Bureau Veritas in Adelaide using laboratory method FA001, 40g Fire assay AAS.		
	Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.			
Drilling techniques	Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	Reverse Circulation drilling utilising a Schramm T450WS with a 700+psi compressor, bit size 140mm.		
Drill sample recovery	Method of recording and assessing core and chip sample recoveries and results assessed.	Bag weights and sizes observed and assessed as representing suitable recoveries.		
	Measures taken to maximise sample recovery and ensure representative nature of the samples.	Drilling capacity suitable to ensure representivity and maximise recovery.		
	Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	There is no known relationship between sample recovery and grade.		





Criteria	JORC Code explanation	Commentary		
Logging	Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged.	All intervals were geologically logged to an appropriate level for exploration purposes. Logging considered qualitative in nature. Chip trays retained for photography. All drillholes have been logged in full.		
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all subsampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	RC drill samples were collected dry with limited wet samples. RC drilling was generally terminated in cases of continual wet samples. RC sample wetness recorded at time of logging. Quality control procedures include submission of CRMs, and blanks with each batch of samples. Sample preparation techniques, where listed, were considered appropriate for the respective sample types. Sub-sampling stages were considered appropriate for exploration. The sample size is considered industry standard for this type of mineralisation and the grain size of the material being sampled.		
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative Company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	Significant intersections verified by Company personnel. No twinning of holes has been undertaken. Primary data entered to digital, validated, and verified offsite. Data stored physically and digitally under company protocols. There has been no adjustment to assay data.		
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	Collar locations were picked up using handheld GPS with accuracy of ±3m. Holes were routinely down hole surveyed and are being assessed for accuracy. The grid system for the Central Gawler Gold Project is GDA94 /MGA Zone 53. Prospect RL control from DGPS data (estimated accuracy ± 0.2m) and GPS (estimated accuracy +-3m). Regional RL control from either: available DTM from airborne surveys or estimation of local RL from local topographic data.		
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	Drill hole spacing is highly variable, ranging from 20m drill hole spacing on 100m spaced drill sections to 100m spaced holes on regional traverses. Data spacing and results are insufficient for resource estimate purposes. No sample compositing has been applied.		
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	Exploration drilling is angled through mineralisation, with no known bias to the sampling of structures assessed to this point. At this early stage of exploration, the certainty of the mineralisation thickness, orientation and geometry is unknown. No sampling bias is considered to have been introduced by the drilling orientation.		
Sample security	The measures taken to ensure sample security.	Sample chain of custody is managed by Indiana. Samples for the Central Gawler Gold Project are stored on site and delivered to the Bureau Veritas laboratory in Adelaide by an Indiana contractor.		
Audits or reviews	The results of any audits or reviews of sampling	No audits or reviews have been noted to date.		





SECTION 2: Reporting of Exploration Results (Criteria listed in the preceding section also apply to this section)

Criteria	JORC Code explanation	Commentary		
Mineral tenement and land tenure status	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to	The Central Gawler Gold Project is located in the Gawler Craton, South Australia. The Project is approximately 650 kilometres north-west of Adelaide. Access to the tenements is via unsealed road near Kingoonya, west of Glendambo, on the Stuart Highway. The Minos Prospect lies on EL 6185, held by wholly owned subsidiary Endeavour Copper Gold Pty Ltd.		
	obtaining a licence to operate in the area.	The tenement is in good standing. No Mining Agreement has been negotiated.		
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	Previous exploration over the area to be acquired has been carried out by many companies over several decades for a range of commodities. Companies and the work completed includes but is not limited to:		
		 Endeavour Resources - gold - RC and DD drilling MIM - gold and base metals - surface geochemistry, airborne and surface based geophysical surveys and AC and RC drilling Grenfell Resources - gold - AC, RC and DD drilling Range River Gold - gold - surface geochemistry and RC drilling Minotaur Exploration - IOCG, gold - gravity, AC and RC drilling CSR - gold - RAB drilling Kennecott - nickel - auger drilling Mithril - nickel - ground geophysics, AC and RC drilling PIMA Mining - gold - surface geochemistry, RAB drilling Santos - gold, tin - RAB and DD drilling Tarcoola Gold - gold - RAB drilling Aberfoyle/Afmeco - uranium, base metals - AC and rotary mud drilling SADME/PIRSA - regional drill traverses - AC, RC and DD drilling 		
Geology	Deposit type, geological setting and style of mineralisation.	The gold mineralisation intersected in drilling to date within the Lake Labyrinth Shear Zone (LLSZ), including the Minos and Ariadne Prospects is concentrated within an intense alteration system (primarily sericite, chlorite, pyrite) of up to 100 metres wide. The majority of the LLSZ is under a thin (2 to 20 metre) veneer of transported cover rendering conventional surface geochemical exploration largely ineffective over the majority of the shear zone.		
Drill hole Information	A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.	All hole collar locations, depths, azimuths and dips are provided within the body of this report for information material to the understanding of the exploration results. All relevant information has been included.		
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	Weighted averages for the Minos mineralisation were calculated using a cut-off grade of 0.5g/t Au with a maximum internal dilution of 2m. Short length of high-grade results use a nominal 5g/t Au cut-off, no minimum reporting length and a maximum internal dilution of 2m. No metal equivalents have been reported.		





Criteria	JORC Code explanation	Commentary
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	Reported intersections are downhole lengths – true widths are unknown at this stage. Mineralisation at Minos is sub vertical. Mineralisation is generally intersected roughly perpendicular to true-width, however try-widths are unknown.
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	Refer to figures and tables in body of text.
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	All significant and relevant intercepts have been reported.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	All relevant exploration data is shown in figures and in text.
Further work	The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).	A discussion of further exploration work is outlined in the body of the text. Additional exploration work of RC drilling is planned.
	 Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	All relevant diagrams and inferences have been illustrated in this report. This program comprised 15 drillholes, Indiana is awaiting the assays from the remaining 10 drillholes, expected March 2022.

